



Förklaring öfver SHELL AUTO-OLJORNA.

SHELL AUTO-OLJORNA tillverkas synnerligen omsorgsfullt samt under noggrannaste kontroll. Särskildt framhålles deras finfina specifika vikt och höga flampunkt. SHELL AUTO-OLJORNA hvarken sota eller becka.

"A"

Tunnare motorolja, som användes under den kalla årstiden.

"B"

Synnerligen tjock motorolja, som användes under sommaren.

"BB"

Något tunnare än föregående. Användes såväl sommar som vinter.

"C"

Denna olja användes i kardan och vexellåda.

"E" Ford

Särskildt tillverkad för Fordautomobiler.

"POLARC"

Denna motorolja användes af Fordautomobiler vintertid.

Hufvudkontor: Helsingfors. **Hufvudnederlag:** Sörnäs. Filialkontor och nederlag: Åbo, Vasa, Viborg, Uleåborg, Kuopio, Sordavala, Kristinestad, Björneborg, Salo, Ekenäs, Borgå, Ny-slott, Lahti, Tammerfors, Joensuu, Jyväskylä, Raumo, Lovisa.

För _____

Från _____

1 gallons kanister

SHELL AUTO-OIL "A"	Fmk
SHELL AUTO-OIL "B"	"
SHELL AUTO-OIL "BB"	"
SHELL AUTO-OIL "C"	"
SHELL AUTO-OIL "E" Ford	"
SHELL AUTO-OIL "POLARC"	"

25 kg. galvaniserat järnfat

SHELL AUTO-OIL "A"	Fmk
SHELL AUTO-OIL "B"	"
SHELL AUTO-OIL "BB"	"
SHELL AUTO-OIL "C"	"
SHELL AUTO-OIL "E" Ford	"
SHELL AUTO-OIL "POLARC"	"

100 kg. galvaniserat järnfat

SHELL AUTO-OIL "A"	Fmk
SHELL AUTO-OIL "B"	"
SHELL AUTO-OIL "BB"	"
SHELL AUTO-OIL "C"	"
SHELL AUTO-OIL "E" Ford	"
SHELL AUTO-OIL "POLARC"	"

I hela fat

SHELL AUTO-OIL "A"	Fmk
SHELL AUTO-OIL "B"	"
SHELL AUTO-OIL "BB"	"
SHELL AUTO-OIL "C"	"
SHELL AUTO-OIL "E" Ford	"
SHELL AUTO-OIL "POLARC"	"
VASELIN	"
VASELIN i 25 kg. fat	"

Utan förbindelse.

Anmärkingar

För

Fån

1 gallons kanister

SHELL AUTO-OIL "A"
 SHELL AUTO-OIL "B"
 SHELL AUTO-OIL "B2"
 SHELL AUTO-OIL "C"
 SHELL AUTO-OIL "E" Ford
 SHELL AUTO-OIL "POLARC"

25 kg. galvaniserat jämnt

SHELL AUTO-OIL "A"
 SHELL AUTO-OIL "B"
 SHELL AUTO-OIL "B2"
 SHELL AUTO-OIL "C"
 SHELL AUTO-OIL "E" Ford
 SHELL AUTO-OIL "POLARC"

100 kg. galvaniserat jämnt

SHELL AUTO-OIL "A"
 SHELL AUTO-OIL "B"
 SHELL AUTO-OIL "B2"
 SHELL AUTO-OIL "C"
 SHELL AUTO-OIL "E" Ford
 SHELL AUTO-OIL "POLARC"

1 helst

SHELL AUTO-OIL "A"
 SHELL AUTO-OIL "B"
 SHELL AUTO-OIL "B2"
 SHELL AUTO-OIL "C"
 SHELL AUTO-OIL "E" Ford
 SHELL AUTO-OIL "POLARC"

VASLIN

VASLIN 25 kg för

Upp förhands

För

Från

1 gallons kanister

SHELL AUTO-OIL "A"	Fmk
SHELL AUTO-OIL "B"	"
SHELL AUTO-OIL "BB"	"
SHELL AUTO-OIL "C"	"
SHELL AUTO-OIL "E" Ford	"
SHELL AUTO-OIL "POLARC"	"

25 kg. galvaniserat järnfat

SHELL AUTO-OIL "A"	Fmk
SHELL AUTO-OIL "B"	"
SHELL AUTO-OIL "BB"	"
SHELL AUTO-OIL "C"	"
SHELL AUTO-OIL "E" Ford	"
SHELL AUTO-OIL "POLARC"	"

100 kg. galvaniserat järnfat

SHELL AUTO-OIL "A"	Fmk
SHELL AUTO-OIL "B"	"
SHELL AUTO-OIL "BB"	"
SHELL AUTO-OIL "C"	"
SHELL AUTO-OIL "E" Ford	"
SHELL AUTO-OIL "POLARC"	"

I hela fat

SHELL AUTO-OIL "A"	Fmk
SHELL AUTO-OIL "B"	"
SHELL AUTO-OIL "BB"	"
SHELL AUTO-OIL "C"	"
SHELL AUTO-OIL "E" Ford	"
SHELL AUTO-OIL "POLARC"	"
VASELIN	"
VASELIN i 25 kg fat	"

Utan förbindelse.

ANALYS.

"A"

Spec. v.	c.	0,911
Flamp.	"	222
Visc. 50°C	"	9
Frysp.	"	-6°

"B"

Spec. v.	"	0,921
Flamp.	"	238
Visc. 50°C	"	17
Frysp.	"	-1°

"BB"

Spec. v.	"	0,915
Flamp.	"	226
Visc. 50°C	"	11
Frysp.	"	-1°

"C"

Spec. v.	"	0,906
Flamp.	"	290
Visc. 50°C	"	30

"E" Ford

Spec. v.	"	0,915
Flamp.	"	205
Visc. 50°C	"	4,5
Frysp.	"	-18°

"POLARC"

Spec. v.	"	0,905
Flamp.	"	215
Visc. 50°C	"	5,1
Frysp.	"	-15°